

## ecomix XS

2-component mixing and metering unit



• The **ecomix XS** is a solid and powerful mixing and metering unit, which is uncompromisingly geared to functionality. • Special attention has been paid to maintainability and robustness by choosing German quality components only. • The **ecomix XS** combines well proven technology with an unbeatable cost / performance ratio.

🏠 Jebel Ali Free Zone  
P.O. Box 261693  
Dubai, United Arab Emirates

☎ +971 4 421 81 71  
📠 +971 4 421 88 12

✉ info@emm-equipment.com  
🌐 www.emm-equipment.com

## ecomix XS

2-component mixing and metering unit

### technical data

outflow max.	3.500 g/min.*
A-side powered	hydraulic
B-side powered	pneumatic
power supply	3 x 400 V + N + PE / 3,8 kW
compressed air requirement	6 bar
dimensions l x w x h / with arm	1.500 x 1.000 x 1.800 / 2.500 mm
standard swivel arm length	1.900 mm
standard hose length	2.500 mm
weight	650 kg
<b>article number</b>	<b>2252 - 0001 - 1000</b>

\* depends on viscosity, temperature, charge etc.



mixing ratio control

### equipment

- Siemens relay control
- pot life control with visual and audible warning signal
- overpressure safety device
- material shortage control
- two-hand safety control
- drum empty control with pump shutdown
- base purging
- waste optimized following plate
- maintenance-free pump sealing system
- infinitely adjustable mixing ratio
- mixing ratio control
- optimized change of drums (base plate with notches for jack lift)
- 200 l A-following plate / 20 l B-following plate

### optional equipment

- heated following plate A-component
- purge pump
- mobile unit with wheels

further options on request