

## monoflow 20 / 200

pneumatic mono - component sealing unit



**monoflow 20**



**monoflow 200**

- Our hand sealing units are very strong and powerful machines that fulfil all requirements of the processing of modern mono-component sealants and adhesives in a superior way.
- A solid construction guarantees easy handling and maintainability on a high standard.

# monoflow 20 / 200

pneumatic mono - component sealing unit

## technical data

	monoflow 20	monoflow 200
output	max. 2.500 g / min.	max. 2.500 g / min.
pneumatic requirements	6 bar, 600 l / min.	6 bar, 600 l / min.
dimensions (l x w x h)	600 x 400 x 1.300 mm	1.000 x 1.150 x 1.800 mm
weight	250 kg	450 kg
<b>article number</b>	<b>2111-0001-1000</b>	<b>2113-0001-1000</b>

\* depending on viscosity, temperature, batch etc. of material

### standard equipment monoflow 20

- teflon-coated following plate for 20 l hobcock
- 2.5 m water-vapour tight high pressure teflon hose
- 2 lifting columns
- high pressure sealing gun
- mobile unit on wheels

### special equipment monoflow 20

- teflon-coated following plate for 200 l barrel
- sealing gun Ultra-Lite
- material pressure regulator for pulsation reduction
- drum empty control with pump stop
- heated following plate
- mobile unit on wheels
- cartridge filling unit
- swivel arm

### standard equipment monoflow 200

- 2.5 m water-vapour tight high pressure teflon hose
- 2 lifting columns
- high pressure sealing gun

### special equipment monoflow 200

- sealing gun Ultra-Lite
- material pressure regulator for pulsation reduction
- drum empty control with pump stop
- cartridge filling unit

further options on request